

# BI- II SERIES Washdown Battery Operated Indicator



## FEATURES

- Simple outdoor operation with battery
- Using dry battery (Mn : Approx. 50 hr, Alkaline : Approx. 150 hr) or rechargeable battery (Approx. 70hr)
- Charging time : 4 ~ 6hr
- Full digital calibration
- Waterproof (IP 65)
- 6 digit liquid crystal display
- Various options (Mounting tilt bracket)
- Applications : Limit scale, Counting scale, Platform scale
- RS - 232 Interface

## OPTIONS

- Back light display
- Rechargeable battery
- Wall mount tilt bracket

## SPECIFICATIONS

Model	BI-100D BI-100DB	BI-100R BI-100RB
Input Sensitivity	2 $\mu$ V/D	
Load cell Excitation Voltage	DC 5V (up to 4EA)	
A/D Internal Resolution	1/100,000	
A/D External Resolution	1/10,000(Max)	
Display	LCD 6 digit (24mm)	
Power Source	DC 9V (1.5V $\times$ 6EA) Mn Battery	DC 7.2V (1.2V $\times$ 6EA) Rec. Battery
Power Consumption	Approx. 0.25W	
Dimension (W $\times$ D $\times$ H)	220 $\times$ 205 $\times$ 90mm	
Product Weight	1.6kg	